

## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of white thermoformed acrylic with laser-cut accent panels and painted canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

- 1 Fixture Number**  
CC-270 16.25"W x 6.5"H x 16.25"L
- 2 Finish**  
Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)

- 3 Lamping**  
All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.


LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38


- Non-LED Lamps**  
3N60: (3) 60 watt incandescent


- 4 LED Color Temp**  
27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K
- 5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)


- 6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)


- 7 Diffuser Options**  
WH: Opal White Acrylic


- 8 Panel Options**
-   
M1

  
M2

  
M3

  
M4

  
M5

  
M6

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Panel