



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** White thermoformed acrylic diffuser with roll formed aluminum front panel and machined bottom finial. Panel fastened to acrylic diffuser with visible black hardware.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

LB-270 8"W x 26.5"H x 4" Ext.
LB-272 6"W x 15"H x 4" Ext.

2 Finish

Finial

Standard Painted Finishes (PT)

Panel

Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Wood Veneer (WV)

3 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-270

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

LB-272

LED Options	Lumens	Wattage
S16	995 (delivered)	16

Non-LED Lamps

1NT60: (1) 60 watt T-10 incandescent

4 LED Color Temp

27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

8 Panel Options



M1



M2



M3



M4



M5



M6

1

Fixture #

2

Finial
(Finish)

2

Panel
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Panel