



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** A thermoformed machined opal white rear housing is standard with a solid aluminum white enameled mounting plate.
- **MOUNTING:** Fixture is supplied with a universal mounting strap assembly that attaches to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- LB-277** 8"W x 25.75"H x 4" Ext.  
**LB-279** 6"W x 14"H x 4" Ext.

### 2 Lamping

LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LB-277

LED Options	Lumens	Wattage
S16	995 (delivered)	16

#### Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

#### LB-279

LED Options	Lumens	Wattage
S16	995 (delivered)	16

#### Non-LED Lamps

1NT60: (1) 60 watt T-10 incandescent

### 3 LED Color Temp

- 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

### 4 LED Dimming

- D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

### 5 Voltage Options

- 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

### 6 Diffuser Options

- WH: White Acrylic  
 CD: Ambia configured diffuser (specify option)

1	2	3	4	5	6
Fixture #	Lamping	Color Temp	Dimming	Voltage	Diffuser