



## Notes

- Specify three digit color suffix with "PT" finish option.
- HOUSING: Consists of a spun aluminum or brass trim ring, acrylic bell diffuser and painted white canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- UL and C-UL listed for dry or damp locations.

**1 Fixture Number**  
DC-850 8.75"H x 23" Dia.

**2 Finish**  
Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)  
Polished Brass (PB)  
Solid Antique Brass (SAB)  
Faux Antique Brass (FAB)

**3 Lamping**  
All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

### DC-850

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

### Non-LED Lamps

- 2N60: (2) 60 watt incandescent
- 2FQ26: (2) 26 watt compact fluorescent
- 1FC22: (1) 22 watt circular compact fluorescent

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

- WH: Opal White Acrylic
- FX: Faux Alabaster Acrylic

**8 Fixture Options**

- FU: Fusing
- EMI: Integral Emergency Battery (Fluor.)
- DM: Fluorescent Dimming
- \*SP: 10kA surge protector (Recommended for D1 dimming option)

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option