

# **Notes**

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of spun aluminum or brass ring trimmed with cast aluminum or brass band, acrylic bell diffuser and choice of stem kit.
- MOUNTING: Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

#### **Fixture Number**

DP-950 9.5"H x 23.5" Dia. 35" Oah. DP-952 11"H x 32" Dia. 49" Oah. DP-956 13.75"H x 40.5" Dia. 63" Oah.

## Finish

Brushed Solid Aluminum (BA) **Cast Band Design** Standard Painted Finishes (PT) Egg & Dart Cast Trim (EGD) Greek Key Cast Trim (GRK) Polished Brass (PB) Solid Antique Brass (SAB) Rope Cast Trim (ROP) Faux Antique Brass (FAB)

## Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DP-950

LED Options	Lumens	Wattage
B47R Uplight + Downlight	2545 up/927 down (delivered)	47

## Non-LED Lamps

3N100: (3) 100 watt incandescent

#### DP-952

LED Options	Lumens	Wattage
B95R Uplight + Downlight	5090 up/1855 down (delivered)	95

## Non-LED Lamps

4N100: (4) 100 watt incandescent

## DP-956

LED Options	Lumens	Wattage
B145R Uplight + Downlight	8309 up/2782 down (delivered)	145

#### **Non-LED Lamps**

6N100: (6) 100 watt incandescent

## **LED Color Temp**

**LED Dimming** 27: 2700K D0: 0-10v

30: 3000K

D1: Triac (Leading Edge)\* 35: 3500K D2: ELV (Trailing Edge) 40: 4000K

# **Voltage Options**

120: 120 volt


277: 277 volt (Not available with incandescent lamp options)

## **Diffuser Options**

WH: White Acrylic

FX: Faux Alabaster Acrylic

## **Stem Options**



(TCH)



Satellite Rods (QAD)