

Ohreo Ceiling (bowl)







1 Fixture Number

DC-881 8.5"H x 18" Dia.

DC-883 8.5"H x 24" Dia.

2 Finish

Standard Painted Finishes (PT)

Brushed Solid Aluminum (BA)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DC-881

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

DC-883

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.