



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of spun aluminum rings and thermoformed opal white acrylic diffuser.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**DS-880** 17.25"W x 8.5"H x 4" Ext.

**2 Finish**  
 Standard Painted Finishes (PT)  
 Brushed Solid Aluminum (BA)

**3 Lamping**  
 LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
S7	612 (delivered)	7

**4 LED Color Temp**  
 27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

**5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

**6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
 WH: Opal White Acrylic

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser