


Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **OAH** is standard unless specified.
- **HOUSING:** Solid spun aluminum cylinder housings with white acrylic cylinder diffusers supported by a cast aluminum center hub.
- **MOUNTING:** Fixture supplied with painted canopy, 60-degree swivel ball and heavy cast aluminum hanger for mounting to structural blocking by others.
- **CIRCUITS:** Two or Three Circuit wiring: Down lamp on circuit #1, Center lamps on circuit #2, Outside lamps on circuit #3 (incand. only).
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- ETL listed to UL standards for dry and damp locations

1 Fixture Number

- CP-253** 34"H x 36" Dia. 72" Oah.
CP-255 42.5"H x 48" Dia. 106" Oah.

2 Finish

- Housing & Trim**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CP-253

Includes (1) 4,984 Lm center downlight and (6) 3,192 Lm outer downlights.
 Integral 120-277v 1-100% dimming drivers compatible with 01-0v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70.

LED Options	Lumens	Wattage
CH304 Body + Downlights	35488 (initial)	304

Non-LED Lamps

3N100 / 1R500 / 6R300: (3) 100 watt incandescent & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base

CP-255

Includes (1) 6,664 Lm center downlight and (6) 3,192 Lm outer downlights.
 Integral 120-277v 1-100% dimming drivers compatible with 01-0v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70.

LED Options	Lumens	Wattage
CH325 Body + Downlights	39232 (initial)	325

Non-LED Lamps

6N100 / 1R500 / 6N100 / 6R300: (6) 100 watt incandescent & (1) 500 watt R40 med. base & (6) 100 watt incandescent & (6) 300 watt R40 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: White Acrylic

1

Fixture #

2

Housing & Trim
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser