



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- LED option includes bottom white acrylic diffuser.
- HOUSING: Consists of a solid spun aluminum cylinder housing with a white acrylic cylinder diffuser.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
LB-158 6"W x 12.5"H x 9" Ext.

2 Finish
Housing & Trim
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)

3 Lamping
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-158

LED Options	Lumens	Wattage
C38	3118 (delivered)	38

Non-LED Lamps
 2N60: (2) 60 watt incandescent

4 LED Color Temp
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
 WH: Opal White Acrylic

