


**1 Fixture Number**

CP-253 34"H x 36" Dia. 72" Oah.  
CP-255 42.5"H x 48" Dia. 106" Oah.

**2 Finish**
**Housing & Trim**

Brushed Solid Aluminum (BA)  
Standard Painted Finishes (PT)

**3 Lamping**

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**CP-253**

Includes (1) 4,984 Lm center downlight and (6) 3,192 Lm outer downlights.

Integral 120-277v 1-100% dimming drivers compatible with 01-0v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70.

**LED Options**

LED Options	Lumens	Wattage
CH304 Body + Downlights	35488 (initial)	304

**Non-LED Lamps**

3N100 / 1R500 / 6R300: (3) 100 watt incandescent & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base

**CP-255**

Includes (1) 6,664 Lm center downlight and (6) 3,192 Lm outer downlights.

Integral 120-277v 1-100% dimming drivers compatible with 01-0v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70.

**LED Options**

LED Options	Lumens	Wattage
CH325 Body + Downlights	39232 (initial)	325

**Non-LED Lamps**

6N100 / 1R500 / 6N100 / 6R300: (6) 100 watt incandescent & (1) 500 watt R40 med. base & (6) 100 watt incandescent & (6) 300 watt R40 med. base

**4 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

B60: 60-deg. beam reflector

B90: 90-deg. beam reflector

CON: Concentric Ring Louver (approx. 50-deg. beam)

**7 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**

WH: White Acrylic

<b>1</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>	<b>8</b>
Fixture #	Housing & Trim (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser