



**Notes**

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Spun aluminum housing and top cover.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**

- DP-770** 1.375"H x 24" Dia. 36" Oah.
- DP-774** 1.875"H x 36" Dia. 36" Oah.
- DP-776** 2"H x 48" Dia. 36" Oah.

**2 Finish Housing**

- Standard Painted Finishes (PT)
- Brushed Solid Aluminum (BA)

**3 Lamping**

Includes integral, canopy, or remote-mounted 120-277v 10-100% dimming drivers compatible with 0-10v controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DP-770**

LED Options	Lumens	Wattage
O30	1991 (delivered)	30

**DP-774**

LED Options	Lumens	Wattage
O45	3079 (delivered)	45

**DP-776**

LED Options	Lumens	Wattage
O62	4188 (delivered)	62

**4 LED Color Temp**

- 30: 3000K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v

**6 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

- AWH: Satin Ice White

**8 Stem Options**



Aircraft Cable (CBL)

**9 Fixture Options**

- DKC: Disk ceiling driver canopy
- PDT: Driver housing suspended above fixture
- REM: Remote driver box

1	2	3	4	5	6	7	8	9
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Stem	Fixture Option