



## Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Spun aluminum housing and top cover.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**DP-770** 1.375"H x 24" Dia. 36" Oah.

**DP-774** 1.875"H x 36" Dia. 36" Oah.

**DP-776** 2"H x 48" Dia. 36" Oah.

### 2 Finish

#### Housing

Standard Painted Finishes (PT)

Brushed Solid Aluminum (BA)

### 3 Lamping

Includes integral, canopy, or remote-mounted 120-277v 10-100% dimming drivers compatible with 0-10v controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DP-770

LED Options	Lumens	Wattage
O30	1991 (delivered)	30

#### DP-774

LED Options	Lumens	Wattage
O45	3079 (delivered)	45

#### DP-776

LED Options	Lumens	Wattage
O62	4188 (delivered)	62

### 4 LED Color Temp

30: 3000K

40: 4000K

### 5 LED Dimming

D0: 0-10v

### 6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

AWH: Satin Ice White

### 8 Stem Options



Aircraft Cable  
(CBL)

### 9 Fixture Options

DKC: Disk ceiling driver canopy

PDT: Driver housing suspended above fixture

REM: Remote driver box

1

Fixture #

2

Housing  
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Stem

9

Fixture Option