



1 Fixture Number

- DP-770** 1.375"H x 24" Dia. 36" Oah.
- DP-774** 1.875"H x 36" Dia. 36" Oah.
- DP-776** 2"H x 48" Dia. 36" Oah.

2 Finish Housing

- Standard Painted Finishes (PT)
- Brushed Solid Aluminum (BA)

3 Lamping

Includes integral, canopy, or remote-mounted 120-277v 10-100% dimming drivers compatible with 0-10v controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-770

LED Options	Lumens	Wattage
O30	1991 (delivered)	30

DP-774

LED Options	Lumens	Wattage
O45	3079 (delivered)	45

DP-776

LED Options	Lumens	Wattage
O62	4188 (delivered)	62

4 LED Color Temp

- 30: 3000K
- 40: 4000K

5 LED Dimming

- D0: 0-10v

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- AWH: Satin Ice White

8 Stem Options



Aircraft Cable (CBL)

9 Fixture Options

- DKC: Disk ceiling driver canopy
- PDT: Driver housing suspended above fixture
- REM: Remote driver box

1

Fixture #

2

Housing (Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Stem

9

Fixture Option