

**1 Fixture Number**

- DP-43-30** 6"H x 30" Dia. 36" Oah.
- DP-43-36** 7"H x 36" Dia. 36" Oah.

**2 Finish**

- |                                 |                                |
|---------------------------------|--------------------------------|
| <b>Trim ring, stem, canopy.</b> | <b>Perforated bowl</b>         |
| Standard Painted Finishes (PT)  | Brushed Solid Aluminum (BA)    |
|                                 | Standard Painted Finishes (PT) |

**3 Lamping**

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**DP-43-30**

LED Options	Lumens	Wattage
B48 Downlight + Uplight (48w)	1402 up/1533 down (delivered)	48

**Non-LED Lamps**

6N60: (6) 60 watt incandescent

**DP-43-36**

LED Options	Lumens	Wattage
B96 Downlight + Uplight (96w)	2804 up/3066 down (delivered)	96

**Non-LED Lamps**

6N75: (6) 75 watt incandescent

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K


**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**7 Stem Options**



<b>1</b>	<b>2</b>	<b>2</b>	<b>3</b>	<b>4</b>	<b>5</b>	<b>6</b>	<b>7</b>
Fixture #	Trim ring, ste (Finish)	Perforated bowl (Finish)	Lamping	Color Temp	Dimming	Voltage	Stem