



## Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Aluminum extrusion with integral LED board channel, heat sink, and acrylic blade support. Machined aluminum components.
- ACRYLIC: Clear 1/8" acrylic panels with laser-etched optical pattern to maximize light output and minimize glare.
- MOUNTING: Mounts to a standard octagonal junction box, mounting hardware provided by others.
- ETL listed to UL standards for dry and damp locations.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
W-122 11"W x 13"H x 1.75" Ext.

**2 Finish**  
Standard Painted Finishes (PT)

**3 Lamping**  
Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

W-122

LED Options	Lumens	Wattage
W7	640 (delivered)	7

**4 LED Color Temp**  
40: 4000K

**5 LED Dimming**  
D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**  
120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
PLG: Planar Optical LightGuide

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser