



Planar Horizontal Core Pendant











1 Fixture Number

P-106 48.75"W x 10"H x 48.75"L x 13" Dia. 34" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

Includes constant current 1-100% dimming drivers mounted in ceiling canopy (or remote). Compatible with 0-10v, Triac, and ELV dimming controls. All LEDs are 80+ CRI, 50,000 hr. L70. Downlight separately circuited.

P-106

LED downlight is COB array producing 3,942 lumens @ 4000K.

LED Options	Lumens	Wattage
X54 Blades Only (54w)	6505 (delivered)	54
X89 Blades (54w) + Downlight (35w)	6505 blades/3098 dn (delivered)	89

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Downlight Optics Options

B30: 30-deg. beam reflector
B60: 60-deg. beam reflector
B90: 90-deg. beam reflector

7 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

PLG: Planar Optical LightGuide

9 Panel Options



HC HD HS

1	2	3	4	5	6	7	8	9
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser	Panel

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.