



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Aluminum extrusion with integral LED board channel, heat sink, and acrylic blade support. Machined aluminum components.
- ACRYLIC: Clear 1/8" acrylic panels with laser-etched optical pattern to maximize light output and minimize glare.
- MOUNTING: Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box. OAH is standard unless specified.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**P-101** 24.75"W x 8"H x 24.75"L x 13" Dia. 32" Oah.

**2 Finish**  
 Standard Painted Finishes (PT)

**3 Lamping**  
 Includes constant current 1-100% dimming drivers mounted in ceiling canopy (or remote). Compatible with 0-10v, Triac, and ELV dimming controls. All LEDs are 80+ CRI, 50,000 hr. L70. Downlight separately circuited.  
**P-101**  
 LED downlight is COB array producing 3,942 lumens @ 4000K.

LED Options	Lumens	Wattage
X27 Blades Only (27w)	3069 (delivered)	27
X62 Blades (27w) + Downlight (35w)	3069 blades/3089 dn (delivered)	62

**4 LED Color Temp**  
 40: 4000K

**5 LED Dimming**  
 D0: 0-10v  
 D1: Triac (Leading Edge)\*  
 D2: ELV (Trailing Edge)

**6 Downlight Optics Options**  
 B30: 30-deg. beam reflector  
 B60: 60-deg. beam reflector  
 B90: 90-deg. beam reflector

**7 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**  
 PLG: Planar Optical LightGuide

**9 Panel Options**



HC

HD

HS

1

2

3

4

5

6

7

8

9

Fixture #

Finish  
(Finish)

Lamping

Color Temp

Dimming

Downlight Opti

Voltage

Diffuser

Panel