



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Aluminum extrusion with integral LED board channel, heat sink, and acrylic blade support. Machined aluminum components.
- **ACRYLIC:** Clear 1/8" acrylic panels with laser-etched optical pattern to maximize light output and minimize glare.
- **MOUNTING:** Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
OAH is standard unless specified.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

P-101 24.75"W x 8"H x 24.75"L x 13" Dia. 32" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

Includes constant current 1-100% dimming drivers mounted in ceiling canopy (or remote). Compatible with 0-10v, Triac, and ELV dimming controls. All LEDs are 80+ CRI, 50,000 hr. L70. Downlight separately circuited.

P-101

LED downlight is COB array producing 3,942 lumens @ 4000K.

LED Options	Lumens	Wattage
X27 Blades Only (27w)	3069 (delivered)	27
X62 Blades (27w) + Downlight (35w)	3069 blades/3089 dn (delivered)	62

4 LED Color Temp

40: 4000K

5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

6 Downlight Optics Options

B30: 30-deg. beam reflector

B60: 60-deg. beam reflector

B90: 90-deg. beam reflector

7 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

PLG: Planar Optical LightGuide

9 Panel Options



HC

HD

HS

1

Fixture #

2

Finish
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Downlight Opti

7

Voltage

8

Diffuser

9

Panel