



1 Fixture Number
P-111 11.5"-12.5"W x 33"H 47.5-49.5 Oah.

2 Finish
 Standard Painted Finishes (PT)

3 Lamping
 Includes constant current 1-100% dimming drivers mounted in ceiling canopy (or remote). Compatible with 0-10v, Triac, and ELV dimming controls. All LEDs are 80+ CRI, 50,000 hr. L70. Downlight separately circuited.

LED Options	Lumens	Wattage
X84 Blades Only (84w)	8620 (delivered)	84
X119 Blades (84W) + Downlight (35w)	11872 (delivered)	119

4 LED Color Temp
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options
 B30: 30-deg. beam reflector
 B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector

7 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options
 PLG: Planar Optical LightGuide

9 Panel Options



1

2

3

4

5

6

7

8

9

Fixture #

Finish
(Finish)

Lamping

Color Temp

Dimming

Downlight Opti

Voltage

Diffuser

Panel