



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of white thermoformed acrylic with laser-cut accent panels and painted canopy.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- UL and C-UL listed for dry or damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
CC-086 16.25"W x 6.5"H x 16.25"L

2 Finish

Trim	Bar Trim
Brushed Solid Aluminum (BA)	Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)
	Wood Trim (WT)

3 Lamping
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
C26	2178 (delivered)	26
C38	3118 (delivered)	38

Non-LED Lamps
 3N60: (3) 60 watt incandescent
 4F18: (4) 18 watt compact fluorescent

4 LED Color Temp
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
 CB: Cobalt Blue Acrylic
 PF: Perforated Aluminum
 WH: Opal White Acrylic

8 Fixture Options
 EMI: Integral Emergency Battery (Fluor.)

1	2	2	3	4	5	6	7	8
Fixture #	Trim (Finish)	Bar Trim (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Fixture Option