



**1 Fixture Number**

- LP-091** 22"H x 9.5" Dia. 48" Oah.
- LP-092** 30"H x 11.5" Dia. 68" Oah.
- LP-094** 36"H x 13.5" Dia. 86" Oah.

**2 Finish**

- |                                |                                |
|--------------------------------|--------------------------------|
| <b>Trim</b>                    | <b>Bar trim</b>                |
| Brushed Solid Aluminum (BA)    | Brushed Solid Aluminum (BA)    |
| Standard Painted Finishes (PT) | Standard Painted Finishes (PT) |
| Brushed Solid Brass (BB)       | Brushed Solid Brass (BB)       |
| Polished Brass (PB)            | Polished Brass (PB)            |
|                                | Wood Trim (WT)                 |

**3 Lamping**

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LP-091**

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

**Non-LED Lamps**

1N200: 200 watt A-21 med. base

**LP-092**

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P88 Body (40w) + Downlight (48w)	8128 (delivered)	88
U18 Optional Uplight (18w)	1613 (delivered)	18

**Non-LED Lamps**

8N75 / 1R300: (8) 75 watt incandescent & (1) 300 watt R40 med. base

**LP-094**

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

**Non-LED Lamps**

10N100 / 1R500: (10) 100 watt incandescent & (1) 500 watt R40 med. base

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

- B60: 60-deg. beam reflector
- B90: 90-deg. beam reflector
- CON: Concentric Ring Louver (approx. 50-deg. beam)
- ECR: Black Egg Crate Louver (approx. 40-deg. beam)

**7 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**

- WH: White Acrylic

