



Notes

- OAH is standard unless specified.
- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Four machined aluminum, brass, or wood trim bars over an extruded white acrylic cylinder diffuser.
- MOUNTING: Fixture supplied with painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- CIRCUITS: Dual-level circuiting for interior lamps/downlight standard.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LP-091** 22"H x 9.5" Dia. 48" Oah.
LP-092 30"H x 11.5" Dia. 68" Oah.
LP-094 36"H x 13.5" Dia. 86" Oah.

2 Finish

Trim

- Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Brushed Solid Brass (BB)
 Polished Brass (PB)

Bar trim

- Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Brushed Solid Brass (BB)
 Polished Brass (PB)
 Wood Trim (WT)

3 Lamping

LED options includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LP-091

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

Non-LED Lamps

1N200: 200 watt A-21 med. base

LP-092

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P88 Body (40w) + Downlight (48w)	8128 (delivered)	88
U18 Optional Uplight (18w)	1613 (delivered)	18

Non-LED Lamps

8N75 / 1R300: (8) 75 watt incandescent & (1) 300 watt R40 med. base

LP-094

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

Non-LED Lamps

10N100 / 1R500: (10) 100 watt incandescent & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)
 ECR: Black Egg Crate Louver (approx. 40-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: Opal White Acrylic

1	2	2	3	4	5	6	7	8
Fixture #	Trim (Finish)	Bar trim (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser