



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Solid machined aluminum or brass bar details over a thermoformed acrylic diffuser.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
LB-095 7"W x 16"H x 4" Ext.

2 Finish
Housing
White painted finish (WHITE)

Bar Trim
Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)
Brushed Solid Brass (BB)
Polished Brass (PB)
Wood Trim (WT)

3 Lamping
LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-095

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps
2NT60: (2) 60 watt T-10 incandescent

4 LED Color Temp
27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming
D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options
120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
WH: Opal White Acrylic
FX: Faux Alabaster Acrylic

1	2	2	3	4	5	6	7
Fixture #	Housing (Finish)	Bar Trim (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser