



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of white thermoformed acrylic with laser-cut accent panels and painted canopy.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
CC-260 16.25"W x 6.5"H x 16.25"L

2 Finish
Trim
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Faux Antique Brass (FAB)

3 Lamping
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CC-260

| LED Options | Lumens | Wattage |
|-------------|------------------|---------|
| C26 | 2178 (delivered) | 26 |
| C38 | 3118 (delivered) | 38 |

Non-LED Lamps

3N60: (3) 60 watt incandescent

4 LED Color Temp
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
 WH: Opal White Acrylic

| | | | | | | |
|-----------|------------------|----------|------------|----------|----------|----------|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| Fixture # | Trim (Finish) | Lamping | Color Temp | Dimming | Voltage | Diffuser |