



**Notes**

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Fabricated solid aluminum housing and separate background accent panel. Top and bottom white acrylic diffusers.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**LB-260** 12"W x 12"H x 4" Ext.

**2 Finish**

<b>Housing</b>	<b>Inner Panel</b>
Brushed Solid Aluminum (BA)	Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)
Faux Antique Brass (FAB)	Faux Antique Brass (FAB)
	Distressed Brass (DB)
	Distressed Copper (DU)
	Distressed Bronze (DZ)

**3 Lamping**  
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LB-260**

LED Options	Lumens	Wattage
S16	995 (delivered)	16

**Non-LED Lamps**  
 2NT60: (2) 60 watt T-10 incandescent

<b>4 LED Color Temp</b>	<b>5 LED Dimming</b>
27: 2700K	D0: 0-10v
30: 3000K	D1: Triac (Leading Edge)*
35: 3500K	D2: ELV (Trailing Edge)
40: 4000K	

**6 Voltage Options**  
 120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**  
 WH: Opal White Acrylic

