



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Fabricated solid aluminum housing and separate background accent panel. Top and bottom white acrylic diffusers.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**LB-260** 12"W x 12"H x 4" Ext.

**2 Finish**

<b>Housing</b>	<b>Inner Panel</b>
Brushed Solid Aluminum (BA)	Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)
Faux Antique Brass (FAB)	Faux Antique Brass (FAB)
	Distressed Brass (DB)
	Distressed Copper (DU)
	Distressed Bronze (DZ)

**3 Lamping**  
LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LB-260**

LED Options	Lumens	Wattage
S16	995 (delivered)	16

### Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

**4 LED Color Temp**

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

**5 LED Dimming**

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

WH: White Acrylic

1	2	2	3	4	5	6	7
Fixture #	Housing (Finish)	Inner Panel (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser