



1 Fixture Number

- W-101** 6"W x 9"H x 2.5" Dia.
- W-103** 6"W x 8.5"H x 2.5" Dia.
- W-105** 6"W x 8.5"H x 2.5" Dia.
- W-107** 6"W x 8.5"H x 2.5" Dia.

2 Finish

- Housing**
- Standard Painted Finishes (PT)

3 Lamping

- Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

W-101

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

W-103

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

W-105

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

W-107

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- AWH: Satin Ice White
- ALG: Satin Ice Light Green
- ACR: Cherry Red
- ASB: Sky Blue
- APN: Pine
- AMD: Mandarin
- FMC: Mica

1

Fixture #

2

Housing
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser