



1 Fixture Number

- W-100** 6"W x 7"H x 2.5" Dia.
- W-102** 6"W x 6.5"H x 2.5" Dia.
- W-104** 6"W x 6"H x 2.5" Dia.
- W-106** 6"W x 6.5"H x 2.5" Dia.

2 Finish

- Housing**
- Standard Painted Finishes (PT)

3 Lamping

- Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

W-100

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

W-102

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

W-104

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

W-106

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

1

Fixture #

2

Housing
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage