


W-100



W-102



W-104



W-106

**1 Fixture Number**

W-100	6"W x 7"H x 2.5" Dia.
W-102	6"W x 6.5"H x 2.5" Dia.
W-104	6"W x 6"H x 2.5" Dia.
W-106	6"W x 6.5"H x 2.5" Dia.

**2 Finish**
**Housing**

Standard Painted Finishes (PT)

**3 Lamping**

Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**W-100**

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

**W-102**

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

**W-104**

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

**W-106**

LED Options	Lumens	Wattage
W14 Uplight (7w) + Downlight (7w)	1021 (delivered)	14

**4 LED Color Temp**

27: 2700K

30: 3000K

35: 3500K

40: 4000K

**5 LED Dimming**

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

**6 Voltage Options**

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

