



- 1 Fixture Number**
DP-750 14"W x 3"H x 14.5"L 36" Oah.
DP-752 29"W x 4.5"H x 29.75"L 48" Oah.

- 2 Finish**
Housing, Stem & Canopy
 Standard Painted Finishes (PT)

- 3 Lamping**
 LED option includes remote or canopy-mounted 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LED Options	Lumens	Wattage
P26 (1) 26-watt LED array	2835 (initial)	26

LED Options	Lumens	Wattage
P84 Uplight + Downlight	12,683 Initial	84

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K
- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WH: White Acrylic

- 8 Fixture Options**
 REM: Remote driver box
 DKC: Disk ceiling driver canopy

