









# **Notes**

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of heavy gauge extruded aluminum corner posts, solid cast aluminum end caps and laser-cut aluminum trim panels.
- MOUNTING: Fixture supplied with mounting template, gasketed mounting plate, and visible hardware. Fixture mounts to 1/4-20 studs attached to structural blocking provided by installing electrician. Standard octagonal junction box required (preferred box placement at bottom arm).
- ETL listed to UL standards for wet locations.
- Fluorescent and metal halide ballasts rated to 22-degree F
- All MH lamp options include integral electronic ballast.

Fixture Number

**DE-210** 13.25"W x 30"H x 16" Ext. **DE-211** 19.75"W x 45"H x 23.25" Ext.

2 Finish

Frame
Standard Painted Finishes (PT)

**Panels** 

Standard Painted Finishes (PT) Raw Copper (CU)

**Optional Bar Trim on R1 Panel** 

No bar trim on R1 panel (NA) Brushed Stainless Steel (BS) Powder coat paint (PP) Polished stainless steel (PS)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

## DE-210

| LED Options | Lumens         | Wattage |
|-------------|----------------|---------|
| E45         | 3272 (initial) | 45      |
| E45/1QP75   |                |         |

# Non-LED Lamps

3N60: (3) 60 watt incandescent

#### DE-211

| LED Options | Lumens         | Wattage |
|-------------|----------------|---------|
| E67         | 4904 (initial) | 67      |
| E67/1QP120  |                |         |

**LED Dimming** 

D0: 0-10v

## Non-LED Lamps

4N60: (4) 60 watt incandescent

4 LED Color Temp

27: 2700K 30: 3000K

35: 3500K

40: 4000K

6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

FX: Faux Alabaster Acrylic

8 Panel Options











9 Fixture Options

PC: Photo Cell

TAL: Top Acrylic Lens