









Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of heavy gauge extruded aluminum corner posts, solid cast aluminum end caps and laser-cut aluminum trim panels.
- MOUNTING: Fixture supplied with mounting template, gasketed mounting plate, and visible hardware. Fixture mounts to 1/4-20 studs attached to structural blocking provided by installing electrician. Standard octagonal junction box required (preferred box placement at bottom arm).
- ETL listed to UL standards for wet locations.
- Fluorescent and metal halide ballasts rated to 22-degree F
- All MH lamp options include integral electronic ballast.

Fixture Number

DE-210 13.25"W x 30"H x 16" Ext. **DE-211** 19.75"W x 45"H x 23.25" Ext.

2 Finish

Frame
Standard Painted Finishes (PT)

Panels

Standard Painted Finishes (PT) Raw Copper (CU)

Optional Bar Trim on R1 Panel

No bar trim on R1 panel (NA) Brushed Stainless Steel (BS) Powder coat paint (PP) Polished stainless steel (PS)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-210

LED Options	Lumens	Wattage
E45	3272 (initial)	45
E45/1QP75		

Non-LED Lamps

3N60: (3) 60 watt incandescent

DE-211

LED Options	Lumens	Wattage
E67	4904 (initial)	67
E67/1QP120		

LED Dimming

D0: 0-10v

Non-LED Lamps

4N60: (4) 60 watt incandescent

4 LED Color Temp

27: 2700K 30: 3000K

35: 3500K

40: 4000K

6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

FX: Faux Alabaster Acrylic

8 Panel Options











9 Fixture Options

PC: Photo Cell

TAL: Top Acrylic Lens