



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of heavy gauge extruded aluminum corner posts, solid cast aluminum end caps and laser-cut aluminum trim panels.
- **MOUNTING:** Fixture supplied with gasketed mounting plate, and visible hardware. Fixture requires additional support by wall anchors or studs attached to structural blocking provided by installing electrician. Standard octagonal junction box required.
- ETL listed to UL standards for wet locations.
- Fluorescent and metal halide ballasts rated to - 22-degree F
- All MH lamp options include integral electronic ballast.

### 1 Fixture Number

**DE-205** 11"W x 30"H x 5.5" Ext.  
**DE-206** 15.5"W x 45"H x 7.75" Ext.

### 2 Finish

#### Frame

Standard Painted Finishes (PT)

#### Panels

Standard Painted Finishes (PT)  
 Raw Copper (CU)

#### Optional Bar Trim on R1 Panel

No bar trim on R1 panel (NA)  
 Brushed Stainless Steel (BS)  
 Powder coat paint (PP)  
 Polished stainless steel (PS)

### 3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### DE-205

LED Options	Lumens	Wattage
E23	1636 (initial)	23

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

#### DE-206

LED Options	Lumens	Wattage
E34	2452 (initial)	34
E34/1QP75		

#### Non-LED Lamps

4N60: (4) 60 watt incandescent

### 4 LED Color Temp

27: 2700K  
 30: 3000K  
 35: 3500K  
 40: 4000K

### 5 LED Dimming

D0: 0-10v

### 6 Voltage Options

120: 120 volt  
 277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: Opal White Acrylic  
 FX: Faux Alabaster Acrylic

### 8 Panel Options



R1



R2



R3



R4



R5



R6

### 9 Fixture Options

PC: Photo Cell

1

2

2

2

3

4

5

6

7

8

9

Fixture #

Frame  
(Finish)

Panels  
(Finish)

Optional Bar T  
(Finish)

Lamping

Color Temp

Dimming

Voltage

Diffuser

Panel

Fixture Option