



Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- HOUSING: Solid aluminum top and bottom end caps, extruded aluminum corner posts and laser-cut aluminum accent panel. Solid aluminum or brass bar stock accents.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number
LB-077 8"W x 16"H x 4" Ext.

2 Finish

Panel & Trim	Bar Trim
Brushed Solid Aluminum (BA)	Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)
Faux Antique Brass (FAB)	Faux Antique Brass (FAB)
	Brushed Solid Brass (BB)

3 Lamping
 LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LB-077

LED Options	Lumens	Wattage
S7	612 (delivered)	7

Non-LED Lamps
 2NT60: (2) 60 watt T-10 incandescent

4 LED Color Temp	5 LED Dimming
27: 2700K	D0: 0-10v
30: 3000K	D1: Triac (Leading Edge)*
35: 3500K	D2: ELV (Trailing Edge)
40: 4000K	

6 Voltage Options
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options
 WH: Opal White Acrylic
 IV: Ivory acrylic
 FX: Faux Alabaster Acrylic

