



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Solid aluminum top and bottom end caps, extruded aluminum corner posts and laser-cut aluminum accent panel. Solid aluminum or brass bar stock accents.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

**1 Fixture Number**  
**LB-077** 8"W x 16"H x 4" Ext.

**2 Finish**

<b>Panel &amp; Trim</b>	<b>Bar Trim</b>
Brushed Solid Aluminum (BA)	Brushed Solid Aluminum (BA)
Standard Painted Finishes (PT)	Standard Painted Finishes (PT)
Faux Antique Brass (FAB)	Faux Antique Brass (FAB)
	Brushed Solid Brass (BB)

**3 Lamping**  
LED option includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**LB-077**

LED Options	Lumens	Wattage
S7	612 (delivered)	7

### Non-LED Lamps

2NT60: (2) 60 watt T-10 incandescent

**4 LED Color Temp**

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

**5 LED Dimming**

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

**6 Voltage Options**

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

WH: White Acrylic  
IV: Ivory acrylic  
FX: Faux Alabaster Acrylic

1	2	2	3	4	5	6	7
Fixture #	Panel & Trim (Finish)	Bar Trim (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser