



## Notes

- ETL listed to UL standards for dry and damp locations
- LED option replaces bottom louver with white acrylic diffuser.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- OVERALL HEIGHT: OAH includes fixture height plus:  
CPI-561-13: 13" chain to ceiling.  
CPI-561-16: 20" chain to ceiling.  
CPI-561-18: 24" chain to ceiling.
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**CPI-561-13** 7.25"H x 13.25" Dia. 26" Oah.

**CPI-561-16** 9"H x 16.75" Dia. 36" Oah.

**CPI-561-18** 9.5"H x 18" Dia. 42" Oah.

### 2 Finish

Standard Painted Finishes (PT)

### 3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### CPI-561-13

LED Options	Lumens	Wattage
P26 (1) 26-watt LED array	2835 (initial)	26
P38 (1) 38-watt LED array	4092 (initial)	38

#### Non-LED Lamps

3N60: (3) 60 watt incandescent

#### CPI-561-16

LED Options	Lumens	Wattage
P26 (1) 26-watt LED array	2835 (initial)	26
P38 (1) 38-watt LED array	4092 (initial)	38

#### Non-LED Lamps

6N60: (6) 60 watt incandescent

#### CPI-561-18

LED Options	Lumens	Wattage
P26 (1) 26-watt LED array	2835 (initial)	26
P38 (1) 38-watt LED array	4092 (initial)	38

#### Non-LED Lamps

6N60: (6) 60 watt incandescent

### 4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

### 5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

CON: Concentric Ring Louver (approx. 50-deg. beam)

### 7 Voltage Options

120: 120 volt

### 8 Diffuser Options

WH: White Acrylic

IV: Ivory acrylic

FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser