



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box.
- **CIRCUITS:** Wired for one, two or three circuits.
- **OVERALL HEIGHT:** Standard OAH includes fixture height plus 6' main chain to ceiling.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- LPI-308-09** 25.5"H x 9.75" Dia. 98" Oah.
LPI-308-11 29"H x 11.5" Dia. 101" Oah.
LPI-308-13 32.5"H x 13" Dia. 104.5" Oah.
LPI-308-16 51.5"H x 16" Dia. 124" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

LPI-308-09

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27 |

Non-LED Lamps

1N100: (1) 100 watt incandescent

LPI-308-11

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27 |
| P50 Body (14w) + Downlight (36w) | 5881 (initial) | 50 |

Non-LED Lamps

3N60 / 1R300: (3) 60 watt incandescent & (1) 300 watt R40 med. base

LPI-308-13

| LED Options | Lumens | Wattage |
|-----------------------------------|------------------|---------|
| P27 Body only w/bottom lens (27W) | 2730 (delivered) | 27 |
| P63 Body (27w) + Downlight (36w) | 5471 (delivered) | 63 |

Non-LED Lamps

3N60 / 1R500: (3) 60 watt incandescent & (1) 500 watt R40 med. base

LPI-308-16

| LED Options | Lumens | Wattage |
|-----------------------------------|-------------------|---------|
| P54 Body only w/bottom lens (54w) | 5555 (delivered) | 54 |
| P109 Body (54w) + Downlight (55w) | 11760 (delivered) | 109 |
| P150 Body (54w) + Downlight (96w) | 14818 (delivered) | 150 |
| U44 Optional Uplight (44w) | 4038 (delivered) | 44 |

Non-LED Lamps

6N60 / 1R500: (6) 60 watt incandescent & (1) 500 watt R40 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Downlight Optics Options

- B60: 60-deg. beam reflector
 B90: 90-deg. beam reflector
 CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

- WH: White Acrylic
 IV: Ivory acrylic
 FX: Faux Alabaster Acrylic

| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-----------|-----------------|---------|------------|---------|----------------|---------|----------|
| Fixture # | Finish (Finish) | Lamping | Color Temp | Dimming | Downlight Opti | Voltage | Diffuser |