



## Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- MOUNTING: Fixture mounts to a standard octagonal junction box.
- CIRCUITS: Wired for one or two circuits.
- OVERALL HEIGHT: Standard OAH includes fixture height plus 6' main chain to ceiling.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

- LPI-602-08** 19"H x 8" Dia. 91" Oah.
- LPI-602-11** 27"H x 11" Dia. 99" Oah.
- LPI-602-13** 33"H x 13" Dia. 105" Oah.
- LPI-602-16** 39"H x 16" Dia. 111" Oah.

### 2 Finish

Standard Painted Finishes (PT)

### 3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LPI-602-08

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27

#### Non-LED Lamps

1N100: (1) 100 watt incandescent

#### LPI-602-11

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P50 Body (14w) + Downlight (36w)	5881 (initial)	50

#### Non-LED Lamps

3N60 / 1R300: (3) 60 watt incandescent & (1) 300 watt R40 med. base

#### LPI-602-13

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

#### Non-LED Lamps

3N60 / 1R500: (3) 60 watt incandescent & (1) 500 watt R40 med. base

#### LPI-602-16

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P88 Body (40w) + Downlight (48w)	8128 (delivered)	88
P136 Body (40w) + Downlight (96w)	16129 (initial)	136
U18 Optional Uplight (18w)	1613 (delivered)	18

#### Non-LED Lamps

3N60 / 1R500: (3) 60 watt incandescent & (1) 500 watt R40 med. base

### 4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

### 5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

- B60: 60-deg. beam reflector
- B90: 90-deg. beam reflector
- CON: Concentric Ring Louver (approx. 50-deg. beam)

### 7 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

- WH: Opal White Acrylic
- IV: Ivory acrylic
- FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser