



## Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of solid cast aluminum trim panels with fabricated steel corner trim posts.
- **MOUNTING:** Fixture mounts to a standard octagonal junction box. LPI-603-16 must be attached to structure using a ceiling fan rated electrical box. LPI-603-18 requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- **CIRCUITS:** Wired for two circuits standard.
- **OVERALL HEIGHT:** Standard OAH includes fixture height plus 3' chain to spreader and 6' main chain to ceiling.
- ETL listed to UL standards for dry and damp locations
- \*Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

### 1 Fixture Number

**LPI-603-13** 26.25"H x 13" Dia. 134" Oah.

**LPI-603-16** 34"H x 16" Dia. 142" Oah.

**LPI-603-18** 36.5"H x 18" Dia. 145" Oah.

### 2 Finish

Standard Painted Finishes (PT)

### 3 Lamping

LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### LPI-603-13

LED Options	Lumens	Wattage
P27 Body only w/bottom lens (27W)	2730 (delivered)	27
P63 Body (27w) + Downlight (36w)	5471 (delivered)	63

#### Non-LED Lamps

3N60 / 3R75 / 1R300: (3) 60 watt incandescent & (3) 75 watt R30 med. base & (1) 300 watt R40 med. base

#### LPI-603-16

LED Options	Lumens	Wattage
P40 Body only w/bottom lens (40w)	3796 (delivered)	40
P136 Body (40w) + Downlight (96w)	16129 (initial)	136
U18 Optional Uplight (18w)	1613 (delivered)	18

#### Non-LED Lamps

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

#### LPI-603-18

LED Options	Lumens	Wattage
P54 Body only w/bottom lens (54w)	5555 (delivered)	54
P109 Body (54w) + Downlight (55w)	11760 (delivered)	109
P150 Body (54w) + Downlight (96w)	14818 (delivered)	150
U44 Optional Uplight (44w)	4038 (delivered)	44

#### Non-LED Lamps

3N60 / 3R300 / 1R500: (3) 60 watt incandescent & (3) 300 watt R40 med. base & (1) 500 watt R40 med. base

### 4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

### 5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)\*

D2: ELV (Trailing Edge)

### 6 Downlight Optics Options

B60: 60-deg. beam reflector

B90: 90-deg. beam reflector

CON: Concentric Ring Louver (approx. 50-deg. beam)

### 7 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

### 8 Diffuser Options

WH: Opal White Acrylic

IV: Ivory acrylic

FX: Faux Alabaster Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser