



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Consists of fabricated steel trim panels and corner trim posts. Three chains to spreader with single chain to ceiling hanger.
- **MOUNTING:** Structural support is required for this heavy fixture. Requires 2 x 4 blocking or 1/2" IP stud extending 1/2" below finished ceiling through center of octagonal junction box.
- **CIRCUITS:** Wired for two or three circuits with separate neutrals.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.
- **OVERALL HEIGHT:** Standard OAH includes fixture height plus 6' chain to spreader and 6' main chain to ceiling.

1 Fixture Number

CPI-420-38 20"H x 38" Dia. 164" Oah.

CPI-420-38A 20"H x 38" Dia. 164" Oah.

CPI-420-48 22"H x 48" Dia. 166" Oah.

CPI-420-48A 22"H x 48" Dia. 166" Oah.

2 Finish

Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency. Body, uplights, ~~CPI-420-38~~ lights separately circuited.

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P245 Body + Downlights	22344 (initial)	245

Non-LED Lamps

6R300 / 1R500 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 100 watt incandescent

CPI-420-38A

Includes (7) 28w LED downlight and (3) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P329 Body + Downlights + Uplights	31920 (initial)	329

Non-LED Lamps

6R300 / 1R500 / 3R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (3) 300 watt R40 med. base & (6) 100 watt incandescent

CPI-420-48

Includes (7) 28w LED downlight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P259 Body + Downlights	31632 (initial)	259

Non-LED Lamps

6R300 / 1R500 / 6R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (6) 100 watt incandescent

CPI-420-48A

Includes (9) 28w LED downlight and (4) 28w uplight arrays, each producing 3,192 lumens at 3500K.

LED Options	Lumens	Wattage
P427 Body + Downlights + Uplights	50784 (initial)	427

Non-LED Lamps

6R300 / 1R500 / 6R300 / 6N100: (6) 300 watt R40 med. base & (1) 500 watt R40 med. base & (6) 300 watt R40 med. base & (6) 100 watt incandescent

4 LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

5 LED Dimming

D0: 0-10v

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

6 Downlight Optics Options

B60: 60-deg. beam reflector

B90: 90-deg. beam reflector

CON: Concentric Ring Louver (approx. 50-deg. beam)

7 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

8 Diffuser Options

WH: Opal White Acrylic

1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Downlight Opti	Voltage	Diffuser