



**1 Fixture Number**

- CP-102** 3"W x 24"H x 24" Dia. 50" Oah.
- CP-103** 3"W x 27.75"H x 36" Dia. 66" Oah.
- CP-104** 4"W x 37"H x 48" Dia. 87" Oah.
- CP-106** 4"W x 51"H x 72" Dia. 115" Oah.
- CP-108** 4"W x 61.75"H x 96" Dia. 126" Oah.

**2 Finish**

- Housing**
- Standard Painted Finishes (PT)

**3 Lamping**

Includes integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 90 CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**CP-102**

| LED Options                        | Lumens                      | Wattage |
|------------------------------------|-----------------------------|---------|
| CH28 (4) Uplights                  | 2300 up delivered           | 28      |
| DCH28 (4) Downlights               | 2300 down delivered         | 28      |
| CH56 (4) Uplights + (4) Downlights | 2300 up/2300 down delivered | 56      |

**CP-103**

| LED Options                        | Lumens                      | Wattage |
|------------------------------------|-----------------------------|---------|
| CH42 (6) Uplights                  | 3500 up delivered           | 42      |
| DCH42 (6) Downlights               | 3500 down delivered         | 42      |
| CH84 (6) Uplights + (6) Downlights | 3500 up/3500 down delivered | 84      |

**CP-104**

| LED Options                         | Lumens                      | Wattage |
|-------------------------------------|-----------------------------|---------|
| CH55 (8) Uplights                   | 4650 up delivered           | 55      |
| DCH55 (8) Downlights                | 4650 down delivered         | 55      |
| CH111 (8) Uplights + (8) Downlights | 4650 up/4650 down delivered | 111     |

**CP-106**

| LED Options                           | Lumens                      | Wattage |
|---------------------------------------|-----------------------------|---------|
| CH83 (12) Uplights                    | 7000 up delivered           | 83      |
| DCH83 (12) Downlights                 | 7000 down delivered         | 83      |
| CH165 (12) Uplights + (12) Downlights | 7000 up/7000 down delivered | 165     |

**CP-108**

| LED Options                           | Lumens                      | Wattage |
|---------------------------------------|-----------------------------|---------|
| CH110 (16) Uplights                   | 9350 up delivered           | 110     |
| DCH110 (16) Downlights                | 9350 down delivered         | 110     |
| CH220 (16) Uplights + (16) Downlights | 9350 up/9350 down delivered | 220     |

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)

**6 Downlight Optics Options**

- B25: 25-deg. beam reflector
- B35: 35-deg. beam reflector
- B50: 50-deg. beam reflector

**7 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**8 Diffuser Options**

- ACL: Satin Ice acrylic
- NAD: No acrylic diffusers

**9 Stem Options**



Angled Rods (TST)

1

2

3

4

5

6

7

8

9

Fixture #

Housing (Finish)

Lamping

Color Temp

Dimming

Downlight Opti

Voltage

Diffuser

Stem