



1 Fixture Number

- CP-122** 3"W x 3"H x 24" Dia. 24" Oah.
- CP-123** 3"W x 3"H x 36" Dia. 36" Oah.
- CP-124** 4"W x 3"H x 48" Dia. 48" Oah.
- CP-126** 4"W x 3"H x 72" Dia. 72" Oah.
- CP-128** 4"W x 3"H x 96" Dia. 96" Oah.

2 Finish

- Housing**
- Standard Painted Finishes (PT)

3 Lamping

Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CP-122

LED Options	Lumens	Wattage
GCH28 Downlight	1425 delivered	28
GCH57 Uplight + Downlight	3700 delivered	57

CP-123

LED Options	Lumens	Wattage
GCH42 Downlight	2150 delivered	42
GCH85 Uplight + Downlight	5575 delivered	85

CP-124

LED Options	Lumens	Wattage
GCH56 Downlight	2850 delivered	56
GCH112 Uplight + Downlight	7425 delivered	112

CP-126

LED Options	Lumens	Wattage
GCH84 Downlight	4300 delivered	84
GCH167 Uplight + Downlight	11175 delivered	167

CP-128

LED Options	Lumens	Wattage
GCH111 Downlight	5725 delivered	111
GCH222 Uplight + Downlight	14900 delivered	222

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

- D0: 0-10v
- D1: Triac (Leading Edge)*
- D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WH: White Acrylic

8 Stem Options



Aircraft Cable (CBL)

1	2	3	4	5	6	7	8
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Stem