



## Notes

- CIRCUITS: Two-circuit wiring for uplight/downlight standard.
- CP-126 and CP-128 are shipped in segments and require some assembly.
- DIFFUSER: Bottom white 1/8" thick extruded acrylic lens. Top: Clear 1/8" thick extruded acrylic lens.
- ETL listed to UL standards for dry and damp locations.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Rolled aluminum extrusion. LED Drivers integral for static color models, remote DMX driver for RGBW option.
- MOUNTING: Field-adjustable aircraft cable suspension to separate mounting locations and power cord to painted canopy. OAH is standard unless specified.

### 1 Fixture Number

<b>CP-122</b>	3"W x 3"H x 24" Dia. 24" Oah.
<b>CP-123</b>	3"W x 3"H x 36" Dia. 36" Oah.
<b>CP-124</b>	4"W x 3"H x 48" Dia. 48" Oah.
<b>CP-126</b>	4"W x 3"H x 72" Dia. 72" Oah.
<b>CP-128</b>	4"W x 3"H x 96" Dia. 96" Oah.

### 2 Finish

#### Housing

Standard Painted Finishes (PT)

### 3 Lamping

Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

#### CP-122

LED Options	Lumens	Wattage
GCH28 Downlight	1425 delivered	28
GCH57 Uplight + Downlight	3700 delivered	57

#### CP-123

LED Options	Lumens	Wattage
GCH42 Downlight	2150 delivered	42
GCH85 Uplight + Downlight	5575 delivered	85

#### CP-124

LED Options	Lumens	Wattage
GCH56 Downlight	2850 delivered	56
GCH112 Uplight + Downlight	7425 delivered	112

#### CP-126

LED Options	Lumens	Wattage
GCH84 Downlight	4300 delivered	84
GCH167 Uplight + Downlight	11175 delivered	167

#### CP-128

LED Options	Lumens	Wattage
GCH111 Downlight	5725 delivered	111
GCH222 Uplight + Downlight	14900 delivered	222

### 4 LED Color Temp

27: 2700K  
30: 3000K  
35: 3500K  
40: 4000K

### 5 LED Dimming

D0: 0-10v  
D1: Triac (Leading Edge)\*  
D2: ELV (Trailing Edge)

### 6 Voltage Options

120: 120 volt  
277: 277 volt (Not available with incandescent lamp options)

### 7 Diffuser Options

WH: White Acrylic

### 8 Stem Options



Aircraft Cable  
(CBL)

1	2	3	4	5	6	7	8
Fixture #	Housing (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Stem