




Notes

- CIRCUITS: Two-circuit wiring for uplight/downlight standard.
- CP-126 and CP-128 are shipped in segments and require some assembly.
- DIFFUSER: Bottom white 1/8" thick acrylic lens. Top: Clear 1/8" thick acrylic lens.
- ETL listed to UL standards for dry and damp locations.
- FINISH: Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- HOUSING: Rolled aluminum extrusion. LED Drivers integral for static color models, remote DMX driver for RGBW option.
- MOUNTING: Field-adjustable aircraft cable suspension to separate mouting locations and power cord to painted canopy. OAH is standard unless specified.

1 Fixture Number

CP-122	3"W	x	3"H	x	24" Dia.	24" Oah.
CP-123	3"W	x	3"H	x	36" Dia.	36" Oah.
CP-124	4"W	x	3"H	x	48" Dia.	48" Oah.
CP-126	4"W	x	3"H	x	72" Dia.	72" Oah.
CP-128	4"W	x	3"H	x	96" Dia.	96" Oah.

2 Finish

Housing

Standard Painted Finishes (PT)

3 Lamping

Includes integral 120-277v 1-100% dimming driver compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

CP-122

LED Options	Lumens	Wattage
GCH28 Downlight	1425 delivered	28
GCH57 Uplight + Downlight	3700 delivered	57

CP-123

LED Options	Lumens	Wattage
GCH42 Downlight	2150 delivered	42
GCH85 Uplight + Downlight	5575 delivered	85

CP-124

LED Options	Lumens	Wattage
GCH56 Downlight	2850 delivered	56
GCH112 Uplight + Downlight	7425 delivered	112

CP-126

LED Options	Lumens	Wattage
GCH84 Downlight	4300 delivered	84
GCH167 Uplight + Downlight	11175 delivered	167

CP-128

LED Options	Lumens	Wattage
GCH111 Downlight	5725 delivered	111
GCH222 Uplight + Downlight	14900 delivered	222

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

D0: 0-10v
D1: Triac (Leading Edge)*
D2: ELV (Trailing Edge)

6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

8 Stem Options



Aircraft Cable (CBL)

1 Fixture # | 2 Housing (Finish) | 3 Lamping | 4 Color Temp | 5 Dimming | 6 Voltage | 7 Diffuser | 8 Stem

©2018 Manning Lighting Inc. Sheboygan, WI 53083 Phone: 920-458-2184 Web: manningltg.com Email: info@manningltg.com Design modification rights reserved. Made in USA.