



- 1 Fixture Number**
DP-44-14 12"H x 14" Dia. 38" Oah.
DP-44-16 12"H x 16" Dia. 38" Oah.
DP-44-18 15.5"H x 18" Dia. 42" Oah.

- 2 Finish**
 Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Polished Brass (PB)

- 3 Lamping**
 All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-44-14

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

- Non-LED Lamps**
 1N100: (1) 100 watt incandescent

DP-44-16

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

- Non-LED Lamps**
 1N200: 200 watt A-21 med. base

DP-44-18

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

- Non-LED Lamps**
 1N200: 200 watt A-21 med. base

- 4 LED Color Temp**
 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

- 5 LED Dimming**
 D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

- 6 Voltage Options**
 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

- 7 Diffuser Options**
 WHG: Opal White Glass

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser