



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint or clear lacquer. Specify three digit color suffix with "PT" finish options.
- **OAH** is standard unless specified.
- **HOUSING:** Spun aluminum fitter and opal white glass shade.
- **MOUNTING:** Fixture supplied with canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- ETL listed to UL standards for dry and damp locations.
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

1 Fixture Number

- DP-44-14** 12"H x 14" Dia. 38" Oah.
DP-44-16 12"H x 16" Dia. 38" Oah.
DP-44-18 15.5"H x 18" Dia. 42" Oah.

2 Finish

- Brushed Solid Aluminum (BA)
 Standard Painted Finishes (PT)
 Polished Brass (PB)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-44-14

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

Non-LED Lamps

1N100: (1) 100 watt incandescent

DP-44-16

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

Non-LED Lamps

1N200: 200 watt A-21 med. base

DP-44-18

LED Options	Lumens	Wattage
P20 Uplight + Downlight	2383 (delivered)	20

Non-LED Lamps

1N200: 200 watt A-21 med. base

4 LED Color Temp

- 27: 2700K
 30: 3000K
 35: 3500K
 40: 4000K

5 LED Dimming

- D0: 0-10v
 D1: Triac (Leading Edge)*
 D2: ELV (Trailing Edge)

6 Voltage Options

- 120: 120 volt
 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

- WHG: Opal White Glass

1	2	3	4	5	6	7
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser