



1 Fixture Number

- DE-143** 10"W x 20"H x 12" Ext.
- DE-144** 12"W x 26.5"H x 14" Ext.
- DE-147** 10"W x 20"H x 12" Ext.
- DE-148** 12"W x 26.5"H x 14" Ext.

2 Finish

- | | |
|--------------------------------|--------------------------------|
| Frame | Bars |
| Standard Painted Finishes (PT) | Brushed Stainless Steel (BS) |
| | Standard Painted Finishes (PT) |

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-143

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

DE-144

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

DE-147

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

DE-148

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

4 LED Color Temp

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

5 LED Dimming

D0: 0-10v

6 Voltage Options

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

8 Fixture Options

PC: Photo Cell

1

Fixture #

2

Frame (Finish)

2

Bars (Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Fixture Option