



Notes

- **FINISH:** Finish is low VOC thermo-cure powdercoat paint. Specify three digit color suffix with "PT" finish options.
- **HOUSING:** Spun aluminum end caps and solid stainless steel bar details over an extruded white acrylic cylinder diffuser.
- **MOUNTING:** Fixture supplied with gasketed universal mounting plate for installation over standard octagonal junction box.
- ETL listed to UL standards for wet locations.

1 Fixture Number

DE-143	10"W x 20"H x 12" Ext.
DE-144	12"W x 26.5"H x 14" Ext.
DE-147	10"W x 20"H x 12" Ext.
DE-148	12"W x 26.5"H x 14" Ext.

2 Finish

Frame	Bars
Standard Painted Finishes (PT)	Brushed Stainless Steel (BS)
	Standard Painted Finishes (PT)

3 Lamping

Includes integral wet location rated 120-277v 1-100% dimming driver compatible with 0-10v controls. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DE-143

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

DE-144

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

DE-147

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

DE-148

LED Options	Lumens	Wattage
E22	1636 (initial)	22
E22/1QP75		

Non-LED Lamps

2N60 / 1QP75: (2) 60 watt incandescent & (1) 75 watt PAR30 halogen med. base

4 LED Color Temp

27: 2700K
30: 3000K
35: 3500K
40: 4000K

5 LED Dimming

DO: 0-10v

6 Voltage Options

120: 120 volt
277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options

WH: White Acrylic

8 Fixture Options

PC: Photo Cell

1

Fixture #

2

Frame
(Finish)

2

Bars
(Finish)

3

Lamping

4

Color Temp

5

Dimming

6

Voltage

7

Diffuser

8

Fixture Option