

**1 Fixture Number**

- CP-260** 9"H x 60" Dia. 30" Oah.
- CP-261** 9"H x 60" Dia. 30" Oah.
- CP-262** 10"H x 80" Dia. 42" Oah.
- CP-263** 10"H x 80" Dia. 42" Oah.

**2 Finish**

- Standard Painted Finishes (PT)
- Brushed Solid Aluminum (BA)

**3 Lamping**

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

**CP-260**

LED Options	Lumens	Wattage
CH64 Two Bowls - Up & Downlight	1097 up/1097 dn per bowl (delivered)	64

**Non-LED Lamps**

6N100: (6) 100 watt incandescent

**CP-261**

LED Options	Lumens	Wattage
CH128 Four Bowls - Up & Downlight	1097 up/1097 dn per bowl (delivered)	128

**Non-LED Lamps**

12N100: (12) 100 watt incandescent

**CP-262**

LED Options	Lumens	Wattage
CH129R Two Bowls - Up & Downlight	2545 up/1855 dn per bowl (delivered)	129

**Non-LED Lamps**

8N100: (8) 100 watt incandescent

**CP-263**

LED Options	Lumens	Wattage
CH256R Four Bowls - Up & Downlight	2545 up/1855 dn per bowl (delivered)	256

**Non-LED Lamps**

16N100: (16) 100 watt incandescent

**4 LED Color Temp**

- 27: 2700K
- 30: 3000K
- 35: 3500K
- 40: 4000K

**5 LED Dimming**

- D0: 0-10v
- D1: Triac (Leading Edge)\*
- D2: ELV (Trailing Edge)


**6 Voltage Options**

- 120: 120 volt
- 277: 277 volt (Not available with incandescent lamp options)

**7 Diffuser Options**

- PT: Standard Painted Finishes
- BA: Brushed Solid Aluminum
- WH: White Acrylic
- FX: Faux Alabaster Acrylic

**8 Stem Options**



1	2	3	4	5	6	7	8
Fixture #	Finish (Finish)	Lamping	Color Temp	Dimming	Voltage	Diffuser	Stem