

Notes

- FINISH: Finish is low VOC thermo-cure powdercoat paint or clear lacquer.
 Specify three digit color suffix with "PT" finish options.
- OAH is standard unless specified.
- HOUSING: Consists of an acrylic bowl diffuser or spun aluminum bowl with laser-cut aluminum bar details and optional "FIN" stem kit.
- MOUNTING: Fixture supplied with a painted canopy, 45-degree swivel ball and hanger for mounting to standard octagon junction box.
- ETL listed to UL standards for dry and damp locations
- *Surge protection recommended for use with D1 (Triac/Leading Edge) dimming systems.

Fixture Number

DP-260 6.75"H x 18.75" Dia. 32" Oah.
DP-262 8"H x 26.75" Dia. 34" Oah.
DP-266 10.5"H x 34.5" Dia. 48" Oah.

2 Finish

Brushed Solid Aluminum (BA) Standard Painted Finishes (PT)

3 Lamping

All LED options include integral 120-277v 1-100% dimming drivers compatible with 0-10v, Triac, and ELV controls. Over-current and short-circuit protected. All LEDs are 80+ CRI, 50,000 hr. L70. Wattage listed includes driver efficiency.

DP-260

| LED Options | Lumens | Wattage |
|-------------------------|-------------------------------|---------|
| B32 Uplight + Downlight | 1097 up/1097 down (delivered) | 32 |

Non-LED Lamps

3N100: (3) 100 watt incandescent

DP-262

| LED Options | Lumens | Wattage |
|-------------------------|-------------------------------|---------|
| B64 Uplight + Downlight | 2545 up/1855 down (delivered) | 64 |

Non-LED Lamps

4N100: (4) 100 watt incandescent

DP-266

| LED Options | Lumens | Wattage |
|---------------------------|-------------------------------|---------|
| B145R Uplight + Downlight | 8309 up/2782 down (delivered) | 145 |

LED Dimming

D1: Triac (Leading Edge)*

D2: ELV (Trailing Edge)

D0: 0-10v

Non-LED Lamps

6N100: (6) 100 watt incandescent

LED Color Temp

27: 2700K

30: 3000K

35: 3500K

40: 4000K

6 Voltage Options

120: 120 volt

277: 277 volt (Not available with incandescent lamp options)

7 Diffuser Options


PT: Standard Painted Finishes

BA: Brushed Solid Aluminum

WH: White Acrylic

FX: Faux Alabaster Acrylic

8 Stem Options



9 Fixture Options

DM: Fluorescent Dimming